POWERLINK EP Perkins Series Diesel Generator with Leroy Somer Alternator



Powerful heavy-duty Perkins industrial diesel

Intelligent control - Manual & Remote start

Weather protective and sound attenuated

WPS45S-AU Model: 50Hz Frequency: Fuel type: Diesel Powered by: PERKINS SERIES

415/240V-50Hz-3Phase

Model	WPS45S-AU			
Power(ESP)	kVA/kw	50/40		
Power(PRP)	kVA/kw	45/36		
Voltage	V	415/240		
Fuel Consumption	Litre/hour	Fuel consumption	100% (of the Prime Power)	10.7 L/h
		Fuel consumption	175% (of the Prime Power)	8.2 L/h
		Fuel consumption	150% (of the Prime Power)	5.7 L/h
		Fuel consumption	25% (of the Prime Power)	3.4 L/h
Fuel Tank Capacity	Litre	360		
Noise Level	dB(A)@7m	-		
Dimensions and Weight	Length	Width	Height	Weight
	2338 mm	1080 mm	1701 mm	1390 kg

ENGINE SPECIFICATIONS

Manufacturer	Perkins
Model	1103A-33TG1
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	3
Displacement	3.3L
Bore and Stroke	105 mm × 127 mm
Compression Ratio	17.25
Frequency Regulation, steady state	±0.5%
Governor Type	Mechanical
Total Oil Capacity w/Filters	8.31L
Coolant Capacity	10.2 L



enclosure

and low emissions engine

Comprehensive warranty and service

ALTERNATOR SPECIFICATIONS

Manufacturer	Leroy Somer LSA42.3M7
Phase	3
Power Factor	0.8
Bearing	1
Exciter type	Brushless, SHUNT
Insulation : Class, temperature rise	Н
Degree of protection	IP23
AVR model	R250
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

Engine Air Flow 0.10m³/s(50Hz)

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

|--|

KEY FEATURES

- Easy configuration with InteliConfig
- Remote monitoring
- Cybersecurity by design
- Easy troubleshooting
- Built-in PLC logic
- Flexible platform
- Stand-by and prime power application control
- Zero power mode
- Secure user management





POWER ANYWHERE ANYTIME

MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au | info@macgen.com SALES | SERVICE | SPARES | HIRE | NEW | USED