# PowerLink RK Kubota Series Diesel Generator with Leroy Somer Alternator



Model: PK23S-AU

Frequency: **50Hz**Fuel type: **Diesel** 

Powered by: KUBOTA Engine

- Powerful heavy-duty Kubota industrial diesel and low emissions engine
- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service
- Outlet 4 x 15A

# **TECHNICAL SPECIFICATIONS**

| Model                 | PK23S-AU   |                     |  |         |
|-----------------------|------------|---------------------|--|---------|
| Power(ESP)            | kVA/kW     | 25.3/20.24          |  |         |
| Power(PRP)            | kVA/kW     | 23/18.4             |  |         |
| Structure Type        |            | RS                  |  |         |
| Fuel Consumption      | Litre/hour | Fuel consumption 10 | Fuel consumption 100% (of the Prime Power) |         |
|                       |            | Fuel consumption 75 | 5% (of the Prime Power)                    | 4.1 L/h |
|                       |            | Fuel consumption50  | 0% (of the Prime Power)                    | 2.8 L/h |
|                       |            | Fuel consumption 25 | Fuel consumption 25% (of the Prime Power)  |         |
| Fuel Tank Capacity    | Litre      | 120                 |  |         |
| Noise Level           | dB(A)@7m   | 65.1                |  |         |
| Dimensions and Weight | Length     | Width               | Height                                     | Weight  |
|                       | 2132 mm    | 780 mm              | 1304 mm                                    | 832 kg  |
|                       |            |                     |  |         |

# **ENGINE SPECIFICATIONS**

| Manufacturer          | Kubota           |
|-----------------------|------------------|
| Model                 | V2403-BG         |
| Engine Speed Rated    | 1500 RPM         |
| Cylinder /Arrangement | 4                |
| Displacement          | 2.434 L          |
| Bore and Stroke       | 87 mm × 102.4 mm |
| Compression Ratio     | 23.8             |
| Intake Resistance     | 1.96kPa          |
| Type of Injection     | Direct           |
| Total Oil Capacity    | 76L              |
| Coolant Capacity      | 7.1 L            |



# **ALTERNATOR SPECIFICATIONS**

| Manufacturer                        | Stamford Pl144J |
|-------------------------------------|-----------------|
| Phase                               | 1               |
| Power Factor                        | 0.8             |
| Bearing                             | 1               |
| Exciter type                        | Brushless       |
| Insulation: Class, temperature rise | Н               |
| Degree of protection                | IP23            |
| AVR                                 | Yes             |
| Altitude                            | ≤1000m          |
| Winding Pitch                       | 2/3             |
| Overspeed                           | 2250rpm         |



# **AIR SYSTEM**

| Engine Air Flow | 0.10 m <sup>3</sup> /s(50Hz) |
|-----------------|------------------------------|

Note: All data sheets are for reference only and subject to change without prior notice.

### **CONTROL PANEL**

| PowerLink PLC-920 |
|-------------------|
|-------------------|

### **KEY FEATURES**

- Standard Control Function
- Manual Engine Control Module
- Low Oil Pressure
- High Engine Temperature
- Auxiliary Shutdown
- Over Speed Protection
- Protection Hold-off Timer
- Charge Failure Warning





# MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au | info@macgen.com SALES | SERVICE | SPARES | HIRE | NEW | USED