PowerLink RK Kubota Series Diesel Generator with Leroy Somer Alternator



Model: PK23S-AU

Frequency: **50Hz**Fuel type: **Diesel**

Powered by: **KUBOTA Engine**

- Powerful heavy-duty Kubota industrial diesel and low emissions engine
- Intelligent control Manual & Remote start
- Weather protective and sound attenuated enclosure
- · Comprehensive warranty and service
- Outlet 4 x 15A

TECHNICAL SPECIFICATIONS

Model	PK23S-AU			
Power(ESP)	kVA/kW	25.3/20.24		
Power(PRP)	kVA/kW	23/18.4		
Structure Type		RS		
Fuel Consumption	Litre/hour	Fuel consumption 10	Fuel consumption 100% (of the Prime Power)	
		Fuel consumption 75	5% (of the Prime Power)	4.1 L/h
		Fuel consumption 50% (of the Prime Power)		2.8 L/h
		Fuel consumption 25	Fuel consumption 25% (of the Prime Power)	
Fuel Tank Capacity	Litre	120		
Noise Level	dB(A)@7m	65.1		
Dimensions and Weight	Length	Width	Height	Weight
	2132 mm	780 mm	1304 mm	832 kg

ENGINE SPECIFICATIONS

Manufacturer	Kubota
Model	V2403-M-DI-BG-BBT
Engine Speed Rated	1500 RPM
Cylinder /Arrangement	4
Displacement	2.434 L
Bore and Stroke	87 mm × 102.4 mm
Compression Ratio	23.8
Intake Resistance	1.96kPa
Type of Injection	Direct
Total Oil Capacity	7.6 L
Coolant Capacity	7.1 L



ALTERNATOR SPECIFICATIONS

Manufacturer	Leroy Somer LSA42.3S5
Phase	1
Power Factor	0.8
Bearing	1
Exciter type	Brushless
Insulation: Class, temperature rise	Н
Degree of protection	IP23
AVR	Yes
Altitude	≤1000m
Winding Pitch	2/3
Overspeed	2250rpm



AIR SYSTEM

Engine Air Flow	0.10 m ³ /s(50Hz)

Note: All data sheets are for reference only and subject to change without prior notice.

CONTROL PANEL

PowerLink PLC-920

KEY FEATURES

- Standard Control Function
- Manual Engine Control Module
- Low Oil Pressure
- High Engine Temperature
- Auxiliary Shutdown
- Over Speed Protection
- Protection Hold-off Timer
- Charge Failure Warning





MELBOURNE | SYDNEY | BRISBANE

www.macfarlanegenerators.com.au I info@macgen.com SALES I SERVICE I SPARES I HIRE I NEW I USED